

Technical Data Sheet

DT0090/00

SPECIAL THINNER FOR POLYURETHANES

Supersedes previous issue dated 07.26. 06

DATE 07/22/2015

Technical characteristics:

Specific gravity (kg/l):	0.860 ± 0.030
Flash point:	+36°C
Drying speed (max 100 – min 0):	40
Resistivity (Mohm per cm at 20°C):	300
Shelf-life:	If the product is properly stored, shelf-life is unlimited.

General characteristics

Special thinner for topcoats polyurethanes to be added from 20% to 30% to Part A.

It has a medium to slow drying speed which enables an optimal drying of the coating film and improves its final look.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.