



TYPICAL APPLICATIONS

Masking tape suitable for 80°C 1 hour oven baking. Suitable for miscellaneous industrial, automotive, construction and other painting applications.

ADVANTAGES AND BENEFITS

- Premium water resist paper
- Excellent adhesion to most surfaces
- Easy application on curved profiles and irregular surfaces
- Easy removal
- No residue
- Compatible with solvent based paints and most water based paints
- 80°C 1 hour temperature service

CONSTRUCTION

- Backing: Saturated water resist crepe paper
- Adhesive: Natural rubber & hydrocarbon resins
- Available Color: Green

Green	
24mm x 45m	36 Rolls per carton
48mm x 45m	20 Rolls per carton

TECHNICAL DATA

Masking Tape	METRIC
Paper grammage	70 Gsm
Total thickness	145 Micron
Peel adhesion	2,7 N/cm
Tensile strength	42 N/cm
Elongation at break	10%
Temperature resistance	80°C 1 hour

Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.



KEY FEATURES



ADHERES TO MOST SURFACES



EASY REMOVAL



HIGH TEMPERATURES



WATER RESIST



NO RESIDUE

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.