

SAFETY DATA SHEET

PROPEEL HD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PROPEEL HD
Product number G4600

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PEELABLE COATING

1.3. Details of the supplier of the safety data sheet

Supplier ORAPI APPLIED LIMITED,
SPRING ROAD,
SMETHWICK,
WEST MIDLANDS, B66 1PT, ENGLAND
Tel: 0121-525-4000
Fax: 0121-525-4919
lee.baughan@orapiapplied.com

Contact person Lee Baughan

1.4. Emergency telephone number

Emergency telephone 0121 525 4000 (09:00 - 17:00 hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373
Asp. Tox. 1 - H304
Environmental hazards Not Classified

Human health

The product is irritating to eyes and skin. Contains a substance/a group of substances which may impair fertility. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Physicochemical

The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers.

2.2. Label elements

Pictogram



Signal word

Danger

PROPEEL HD

Hazard statements	<p>H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.</p>
Precautionary statements	<p>P240 Ground/ bond container and receiving equipment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p>
Contains	ACETONE, TOLUENE
Supplementary precautionary statements	<p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P233 Keep container tightly closed. P302+P352 IF ON SKIN: Wash with plenty of water. P308+P313 IF exposed or concerned: Get medical advice/ attention. P314 Get medical advice/ attention if you feel unwell. P331 Do NOT induce vomiting. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE		30-60%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

PROPEEL HD

TOLUENE		10-30%
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-XXXX
Classification		
Flam. Liq. 2 - H225		
Skin Irrit. 2 - H315		
Repr. 2 - H361d		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
CALCIUM CARBONATE		3-10%
CAS number: 1317-65-3	EC number: 215-279-6	
Classification		
Not Classified		
DI-ISONONYL PHTHALATE		3-10%
CAS number: 28553-12-0	EC number: 249-079-5	REACH registration number: 01-2119430798-28-XXXX
Classification		
Not Classified		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
Ingestion	Drowsiness, dizziness, disorientation, vertigo. May cause discomfort if swallowed.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritation of eyes and mucous membranes.

PROPEEL HD

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. The product is highly flammable. May explode when heated or when exposed to flames or sparks. May form explosive mixture with air at very high concentration. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses. Cool containers exposed to flames with water until well after the fire is out. Move containers from fire area if it can be done without risk. Use water spray to reduce vapours. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. No smoking, sparks, flames or other sources of ignition near spillage. Take precautionary measures against static discharges.

6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Absorb spillage with non-combustible, absorbent material. Flush contaminated area with plenty of water. Contain spillage with sand, earth or other suitable non-combustible material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

PROPEEL HD

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with the following materials: Acids. Moisture. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Static electricity and formation of sparks must be prevented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Earth container and transfer equipment to eliminate sparks from static electricity. Take precautionary measures against static discharges.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

DI-ISONONYL PHTHALATE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

ACETONE (CAS: 67-64-1)

DNEL

Industry - Dermal; Long term systemic effects: 186 mg/kg/day

Industry - Inhalation; Short term local effects: 2420 mg/m³

Industry - Inhalation; Long term systemic effects: 1210 mg/m³

Consumer - Oral; Long term : 62 mg/kg/day

Consumer - Dermal; Long term : 62 mg/kg/day

Consumer - Inhalation; Long term : 200 mg/m³

PROPEEL HD

- PNEC**
- Fresh water; 10.6 mg/l
 - Marine water; 1.06 mg/l
 - Sediment (Freshwater); 30.4 mg/kg
 - Sediment (Marinewater); 3.04 mg/kg
 - STP; 29.5 mg/l
 - Soil; 0.112 mg/kg

TOLUENE (CAS: 108-88-3)

- DNEL**
- Workers - Inhalation; Long term systemic effects: 192 mg/m³
 - Workers - Inhalation; Short term systemic effects: 384 mg/m³
 - Workers - Inhalation; Long term local effects: 192 mg/m³
 - Workers - Dermal; Long term systemic effects: 384 mg/m³
 - General population - Inhalation; Long term systemic effects: 56.5 mg/m³
 - General population - Inhalation; Short term systemic effects: 226 mg/m³
 - General population - Inhalation; Long term local effects: 56.5 mg/m³
 - General population - Inhalation; Short term local effects: 226 mg/m³
 - General population - Dermal; Long term systemic effects: 226 mg/kg/day
 - General population - Oral; Long term systemic effects: 8.13 mg/kg/day

- PNEC**
- Fresh water; 0.68 mg/l
 - Sediment (Freshwater); 16.39 mg/l
 - STP; 13.61 mg/l
 - Soil; 2.89 mg/kg
 - Marine water; 0.68 mg/l
 - Sediment (Marinewater); 16.39 mg/kg

DI-ISONONYL PHTHALATE (CAS: 28553-12-0)

- DNEL**
- Workers - Inhalation; Long term systemic effects: 51.72 mg/m³
 - Workers - Dermal; Long term systemic effects: 366 mg/kg/day
 - General population - Inhalation; Long term systemic effects: 15.3 mg/m³
 - General population - Dermal; Long term systemic effects: 220 mg/kg/day
 - General population - Oral; Long term systemic effects: 4.4 mg/kg/day

- PNEC**
- Soil; 30 mg/kg

Soybean oil, epoxidized (CAS: 8013-07-8)

- DNEL**
- Workers - Inhalation; Long term systemic effects: 11.9 mg/m³
 - Workers - Inhalation; Short term systemic effects: 70 mg/m³
 - Workers - Dermal; Long term systemic effects: 1.7 mg/kg/day
 - Workers - Dermal; Short term systemic effects: 10 mg/kg/day
 - General population - Inhalation; Long term systemic effects: 2.8 mg/m³
 - General population - Inhalation; Short term systemic effects: 17.5 mg/m³
 - General population - Dermal; Long term systemic effects: 0.8 mg/kg/day
 - General population - Dermal; Short term systemic effects: 5 mg/kg/day
 - General population - Oral; Long term systemic effects: 0.8 mg/kg/day
 - General population - Oral; Short term systemic effects: 5 mg/kg/day

- PNEC**
- Soil; 6.25 mg/kg

8.2. Exposure controls

PROPEEL HD

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Butyl rubber. Polyvinyl alcohol (PVA). Polytetrafluoroethylene (PTFE, Teflon).

Other skin and body protection

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Wear a full facepiece respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid. Mobile liquid.
Colour	White/off-white.
Odour	Solvent.
Initial boiling point and range	56 - 110 @°C @ 760mmHg
Flash point	- 17°C CC (Closed cup).
Upper/lower flammability or explosive limits	: 1.0
Vapour density	> 1.0
Relative density	0.94 @ 20°C
Solubility(ies)	Slightly soluble in water.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 645 g/litre.
---------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	No particular stability concerns. Avoid the following conditions: Heat, sparks, flames.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
------------------------------------	--

PROPEEL HD

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Heating may generate the following products: Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Harmful: danger of serious damage to health by prolonged exposure through inhalation. Vapours may cause drowsiness and dizziness. Gas or vapour in high concentrations may irritate the respiratory system. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact Irritating to skin. Prolonged or repeated exposure may cause severe irritation. May be absorbed through the skin.

Eye contact Irritating to eyes. Repeated exposure may cause chronic eye irritation. Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards Contains a substance/a group of substances which may damage the unborn child. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache.

Toxicological information on ingredients.

ACETONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 20,000.0

Species Rabbit

Acute toxicity - inhalation

PROPEEL HD

Acute toxicity inhalation 76.0
(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours 76.0
mg/l)

TOLUENE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ 5,000.0
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 12,124.0
mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation 5,320.0
(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours 5,320.0
mg/l)

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

DI-ISONONYL PHTHALATE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ 10,000.0
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,160.0
mg/kg)

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation 4.4
(LC₅₀ dust/mist mg/l)

Species Rat

ATE inhalation 4.4
(dusts/mists mg/l)

COPOLYMER OF VINYL CHLORIDE AND VINYL ACETATE

PROPEEL HD

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

Ecological information on ingredients.

ACETONE

Acute toxicity - fish LC₅₀, 96 hours: 8300 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 8800 mg/l, Daphnia magna

TOLUENE

Acute toxicity - fish LC₅₀, 96 hours: 5.5 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.78 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 10 mg/l, Freshwater algae

DI-ISONONYL PHTHALATE

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 74 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Absorb in vermiculite, dry sand or earth and place into containers. Waste material and any included combustible absorbent and containers should be suitable for incineration at an approved facility.

PROPEEL HD

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	Paint Related Materials (contains Toluene and Acetone)
Proper shipping name (IMDG)	Paint Related Materials (contains Toluene and Acetone)
Proper shipping name (ICAO)	Paint Related Materials (contains Toluene and Acetone)
Proper shipping name (ADN)	Paint Related Materials (contains Toluene and Acetone)

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33

PROPEEL HD

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. GHS: Globally Harmonized System. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. SVHC: Substances of Very High Concern. vPvB: Very Persistent and Very Bioaccumulative. cATpE: Converted Acute Toxicity Point Estimate. EC ₅₀ : 50% of maximal Effective Concentration. DMEL: Derived Minimal Effect Level. UN: United Nations. IBC: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code).
---	---

PROPEEL HD

General information	<p>For further information or advice contact our technical service line during regular office hours on 0121-524-1000.</p> <p>This safety data sheet has been compiled for the product as supplied, properties and hazards will vary if the product is diluted with water or mixed with any other material.</p>
Revision date	27/06/2016
Revision	10
Supersedes date	29/05/2015
SDS status	Approved.
Signature	Health and Safety Manager
Hazard statements in full	<p>H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H361d Suspected of damaging the unborn child by inhalation. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.