

FLORMAX

TECHNICAL DATA

PRODUCT DESCRIPTION	A single pack, quick drying, durable floor paint.			
👁️ FEATURES	Quick Drying Easy to apply Single Pack – no mixing required Tough durable coating Excellent Coverage High Solids			
✓ RECOMMENDED USE	Easy to use floor paint, suitable for coating most floor surfaces Including concrete, steel and timber.			
🔑 PHYSICAL PROPERTIES	Colours:	Green, Grey, Red and Yellow (other colours on request)	Water Resistance: Good Gloss Retention: Good	
	Volume Solids:	50%	Abrasion Resistance: Good	
	Flash Point:	32°C	Solvent Resistance: Good	
	VOC:	420g/litre	Chemical Resistance: Good	
	Gloss:	Semi gloss	Flexibility: Good	
📏 FILM THICKNESS & SPREADING RATE		Minimum	Maximum	Typical
	Film thickness, dry	30	50	50
	Film thickness, wet	75	100	85
	Theoretical spreading rate m ² /l	8	10	8
☑️ SURFACE PREPARATION	All substrates to be free from oil, dirt, rust, grease and any other contaminants. Consult our technical staff for information.			
🌡️ RECOMMENDED TEMPERATURE	Temperature of substrate should be a minimum of 3°C above the dew point, ideally 15-20°C.			
🔧 APPLICATION METHODS	Brush or Roller – Ready for use			
💧 THINNER / CLEANER:	White Spirit PSW205			
🕒 DRYING / OVERCOATING	Surface dry: 60 minutes	To handle: 12 hours	Hard dry: 5 hours	
🔧 SUITABLE PRIMER	Please consult our technical staff for advise.			
🏠 STORAGE	Store in accordance with national regulations, in a cool, well-ventilated area, away from heat and ignition. Keep lids tightly closed. Unopened containers may be stored for up to 2 years.			
👤 HANDLING	Handle with care. Stir thoroughly before use.			
📦 PACK SIZES	5 litre, 20 litre			
⚠️ HEALTH & SAFETY	Please read and observe the safety precautions on the label. Refer to the material safety data sheets for further information.			

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.