














ULTRIMAX Black Nitrile Gloves



TECHNICAL DATA

	PRODUCT DESCRIPTION	Premium quality Black Nitrile gloves that offer greater tensile strength and protection than both Latex and Vinyl. Nitrile gloves offer extra comfort and flexibility.														
	FEATURES	5mil Powder-Free Nitrile	Low odour													
		Non-Sterile	Micro-Textured													
		Non-toxic	AQL 1.5													
		Beaded cuff	Latex Free													
		Ambidextrous														
	PHYSICAL PROPERTIES	<table border="1"> <tr> <td>Sizes:</td> <td>S</td> <td>S80 ± 10 mm min. 240 mm</td> </tr> <tr> <td></td> <td>M</td> <td>95 ± 10 mm min. 240 mm</td> </tr> <tr> <td></td> <td>L</td> <td>110 ± 10 mm min. 240 mm</td> </tr> <tr> <td></td> <td>XL</td> <td>> 110 mm min. 240 mm</td> </tr> </table>	Sizes:	S	S80 ± 10 mm min. 240 mm		M	95 ± 10 mm min. 240 mm		L	110 ± 10 mm min. 240 mm		XL	> 110 mm min. 240 mm		
Sizes:	S	S80 ± 10 mm min. 240 mm														
	M	95 ± 10 mm min. 240 mm														
	L	110 ± 10 mm min. 240 mm														
	XL	> 110 mm min. 240 mm														
		Single wall thickness:	Finger tips 0.13mm Palm 0.10mm Cuff 0.08mm													
			Unaged	Aged												
		Tensile Strength	min. 14.0 MPa	min. 14.0 MPa												
		Elongation	min. 500 %	min. 400 %												
		Strength at Break	min. 6N	min. 6N												
	Shelf Life	5 years														
	HEALTH & SAFETY	89/686/EEC, 93/42/EWG ISO 9001:2008, ISO 13485, CMDCAS 13485 (SGS) EN 455 1-4 EN 420 : 2003 + A 1 : 2009 EN 374 2-3, EN 388 EN 1186: Food Contact Approved (SGS)														
		        														

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.