

ULTRIPRIME ETCH

TECHNICAL DATA

PRODUCT DESCRIPTION	Single pack high build PVB primer
FEATURES	Contains zinc phosphate anti-corrosion pigment No webbing when sprayed Can be over coated with most types of paint finishes Good heat resistance Conforms to BS5493: 1977 Table 4F Part FP2A and FP3A
VISCOSITY	195" B4 / 20°C
PHYSICAL PROPERTIES	Colours: Grey and Black Flash Point: 24°C VOC: 450 g/litre Gloss: Slight sheen Volume Solids: 23%
APPLICATION METHODS	Airless spray / brush – ready for use Conventional spray – up to 20% thinners
THINNER / CLEANER	Ultraprime Etch Thinners T3
DRYING / OVERCOATING	Over coat after 12 hours
DRY FILM THICKNESS	Weld through operation apply 12 – 15 microns
COVERING	8 – 10 sq metres per litre
STORAGE	Store in cool, dry conditions, typically 5-25°C, according to the highly flammable liquids and liquefied petroleum gases regulations.
SHELF LIFE	Usable life 2 years from date of manufacture in unopened containers

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.