

ANTICLIMB

TECHNICAL DATA

PRODUCT DESCRIPTION	Designed for exterior use to deter intruders, does not dry and makes it difficult to climb on.	
👁️ FEATURES	Easy to apply onto masonry, concrete, wood, metal, asbestos	
	Difficult to remove from clothing	
	Display of a clear warning sign is recommended	
✓ RECOMMENDED USE	Only use in areas where legitimate or normal access is not permitted	
🔧 PHYSICAL PROPERTIES	Finish:	Glossy gel
	Viscosity:	Thixotropic (thick gel)
	Volume Solids:	Typically 45%
	Flash Point:	Over 32°C
	VOC:	Typically 580grams/litre
	Specific Gravity:	Typically 0.99
	Flash Point:	>28°C
	Coverage:	Approximately 1sq metre per litre dependent on thickness applied, porous coatings may require additional coats
☰ FILM THICKNESS	DRY: MIN 20 microns, MAX 35 microns	WET: MIN 65 microns, MAX 110 microns
☑️ SURFACE PREPARATION	Surfaces should be dry and free from heavy contamination such as dust oil or grease	
🔧 APPLICATION METHODS	Ready for use, best method by stiff brush, trowel or hand with suitable protection	
💧 THINNER / CLEANER	T7004 (T4)	
🕒 DRYING / OVERCOATING	60 min touch dry / 24 hours hard dry	
	Excellent wet on wet and with itself and most alkyd based paints. Leave primers overnight before over coating with topcoat.	
🏠 STORAGE	Storage should be in accordance with the relevant MSDS. Shelf life; 2 years, in an unopened, original container from date of manufacture.	
⊕ HEALTH & SAFETY	Please read and observe the safety precautions on the label. Refer to the material safety data sheets for further information.	

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.