HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 1

1. PRODUCT AND COMPANY IDENTIFICATION

1.01 Product Name Ultrimax Rocket Accelerator

1.02 Synonyms (General colours)

1.03 Intended Use1.04 Manufacturer/SupplierUltrimax Coatings Ltd

1.05 Address Clayfield Industrial Estate, Tickhill Road, Doncaster, DN4 8QG

1.06 Contact www.ultrimaxcoatings.co.uk

 1.07 Phone Number
 01302 856666

 1.08 Fax Number
 01302 571510

 1.09 Emergency Phone Number
 01302 856666

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Acute Tox. 4: H312; Acute Tox. 4: H332; Skin Irrit. 2: H315; Skin Sens. 1:

H317; Muta. 2: H341; Repr. 1A: H360FD; STOT SE 3: H336; STOT RE 2: H373; Aquatic Chronic

2: H411

2.2 Label elements

Hazard statements: H226 Flammable liquid and vapour

H312+H332 Harmful in contact with skin or if inhaled

H315 Causes skin irritation

H317 May cause an allergic skin reaction H336 May cause drowsiness or dizziness H341 Suspected of causing genetic defects

H360FD May damage fertility. May damage the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H411 Toxic to aquatic life with long lasting effects

Contains: n-butyl acetate, ethylbenzene

Signal words: Warning
Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Precautionary statements: P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe spray, vapours

P263 Avoid contact during pregnancy/while nursing

P273 Avoid release to the environment

P280 Wear face protection, protective clothing, protective gloves

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower P312 Call a doctor if you feel unwell

2.3 Other hazards

Other hazards: No additional information available.

PBT: This substance is not identified as a PBT substance.



Page 2

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous ingredients:

EINECS n-butyl acetate	CAS	CHIP Classification	CLP Classification	Percent
204-658-1	123-86-4	R10; R66; R67	Flam. Liq. 3, H226 STOT SE 3, H336	43-63%
Xylene				
215-535-7	1330-20-7	R10; Xn; R20/21; Xi; R38	Flam. Liq. 3, H226; Acute Tox. 4 (Dermal), H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	23-43%
Ethylbenzene				
202-849-4	100-41-4	F; R11; Xn; R20	Flam. Liq. 2, H225; Acute Tox. 4 (Inhalation), H332; STOT RE 2, H373; Asp. Tox. 1, H304	5-23%

N-BUTYL-2-(1-ETHYLPENTYL)-1,3-0XAZOLIDINE REACH-no 01-0000017206-75

165101-57-5 N; R51/53 Aquatic Chronic 2, H411 <5%

4. FIRST AID MEASURES

4.1 Description of first aid measures

General First-aid measures: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention

Skin contact: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a POISON CENTER or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention or rash occurs: Get medical advice/

attention. Repeated exposure may cause skin dryness or cracking.

Eye contact: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician if you feel unwell.

4.2 Most Important symptoms and effects, both acute and delayed

Symptoms/injuries: Suspected of causing genetic defects. May damage fertility. May damage the unborn child.

Causes damage to organs.

Symptoms/injuries after

inhalation: May cause an allergic skin reaction. May cause drowsiness or dizziness.

Symptoms/injuries after

skin contact: Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Harmful in contact with skin. Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available



HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 3

5. FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2 Special hazards arising from the substance or mixture

Fire hazard: Flammable liquid and vapour.

Explosion hazard: May form flammable/explosive vapour-air mixture.

5.3 Advice for fire-fighters

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting: Do not enter fire area without proper protective equipment, including respiratory protection

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General measures: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking.

Protective equipment: Safety glasses. Protective clothing. Gloves.

Emergency procedures: Evacuate unnecessary personnel.

Protective equipment: Equip clean-up crew with proper protection. Avoid breathing spray, vapours.

Emergency procedures: Ventilate area.

6.2 Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3 Methods and material for containment and cleaning up

Clean-up procedures: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials

6.4 Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.



HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 4

7. HANDLING & STORAGE

7.1 Precautions for safe handling

Additional hazards when processed:

Precautions for safe handling:

Handle empty containers with care because residual vapours are flammable.

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing spray, vapours.

Use only outdoors or in a well-ventilated area.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical, lighting equipment.

Storage conditions: Keep only in the original container in a cool, well ventilated place away from: Ignition

sources, Heat sources, keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Keep container tightly closed.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Sources of ignition. Direct sunlight. Heat sources.

Storage temperature: <25 °C

Storage area: Store in a well-ventilated place. **Special rules on packaging:** Keep only in original container.

7.3 Specific end use(s)

Specific end use(s): No data available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters N-butyl acetate (123-86-4)

United KingdomLocal nameButyl acetateUnited KingdomWEL TWA (mg/m³)724 mg/m³United KingdomWEL TWA (ppm)150 ppmUnited KingdomWEL STEL (mg/m³)966 mg/m³United KingdomWEL STEL (ppm)200 ppm



HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ethylbenzene (100-41-4)

EU Local name Ethylbenzene EU IOELV TWA (mg/m³) 442 mg/m³ EU IOELV TWA (ppm) 100 ppm EU IOELV STEL (mg/m³) 884 mg/m³ FU IOELV STEL (ppm) 200 ppm ΕU Notes Skin

United Kingdom Local name Ethylbenzene United Kingdom WEL TWA (mg/m³) 441 mg/m³ United Kingdom WEL TWA (ppm) 100 ppm United Kingdom WEL STEL (mg/m³) 552 mg/m³ United Kingdom WEL STEL (ppm) 125 ppm United Kingdom Remark (WEL) Sk

Xylene (1330-20-7)

EU Local name Xylene, mixed isomers, pure

 EU
 IOELV TWA (mg/m³)
 221 mg/m³

 EU
 IOELV TWA (ppm)
 50 ppm

 EU
 IOELV STEL (mg/m³)
 442 mg/m³

 EU
 IOELV STEL (ppm)
 100 ppm

 EU
 Notes
 Skin

United Kingdom Local name Xylene, or mixed isomers

United KingdomWEL TWA (mg/m³)220 mg/m³United KingdomWEL TWA (ppm)50 ppmUnited KingdomWEL STEL (mg/m³)441 mg/m³United KingdomWEL STEL (ppm)100 ppmUnited KingdomRemark (WEL)Sk, BMGV

8.2 Exposure controls

Personal protective equipment: Avoid all unnecessary exposure.

Materials for protective clothing:Impermeable clothingHand protection:Wear protective gloves

Eye protection: Chemical goggles or safety glasses **Skin and body protection:** Wear suitable protective clothing

Respiratory protection: Where exposure through inhalation may occur from use, respiratory protection

equipment is recommended

Other information: Do not eat, drink or smoke during use.



HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 6

9. PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:LiquidAppearance:Liquid.Colour:Colourless.Odour:Aromatic.

Odour threshold: No data available pH: No data available Relative evaporation rate: No data available Melting point: No data available Freezing point: No data available Boiling point: No data available

Flash point: 25°C

Auto-ignition temperature: No data available Decomposition temperature: No data available

Flammability (solid, gas): Flammable liquid and vapour

Vapour pressure:

Relative vapour density at 20 °C:

Relative density:

Density:

No data available

Solubility: insoluble in water. Soluble in most organic solvents.

Log Pow:

Viscosity, kinematic:

Viscosity, dynamic:

Explosive properties:

Oxidising properties:

Explosive limits:

No data available

No data available

No data available

9.2 Other information

VOC content:844 g/lVOC content - Actual:844 g/lVOC content - Regulatory:844 g/l

10. STABILITY & REACTIVITY

10.1 Reactivity

No additional information available

10.2 Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture

10.3 Possibilities of hazardous reactions

Not established.

10.4 Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5 Incompatible materials

Strong bases. Strong acids

10.6 Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases



HEALTH AND SAFETY DATA SHEET

Revised 21/06/2017

Page 7

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity: Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

ATE CLP (dermal) 1100 mg/kg bodyweight

 ATE CLP (gases)
 4500 ppmv/4h

 ATE CLP (vapours)
 11.000 mg/l/4h

 ATE CLP (dust,mist)
 1.500 mg/l/4h

Skin corrosion/irritation: Not classified

Repeated exposure may cause skin dryness or cracking

Serious eye damage/irritation: Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation: Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity: Not classified

Based on available data, the classification criteria are not met

Carcinogenicity: Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity: Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity (SE): May cause drowsiness or dizziness.

Specific target organ toxicity (RE): Not classified

Based on available data, the classification criteria are not met

Aspiration hazard: Not classified

Based on available data, the classification criteria are not met

Potential adverse human health

effects and symptoms: Based on available data, the classification criteria are not met.



HEALTH AND SAFETY DATA SHEET

Revised 21/06/2017

Page 8

12. ECOLOGICAL INFORMATION

12.1 Toxicity Ecology - water:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

May cause long-term adverse effects in the environment

12.3 Bio accumulative potential

Not established

12.4 Mobility in soil

No additional information available

12.5 Results of PBT and vPvB assessment

No additional information available

12.6 Other adverse effects

Avoid release to the environment

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Regional legislation (waste):

Disposal must be done according to official regulations.

Waste disposal recommendations:

Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to remove waste in accordance with local and/or national

regulations.

Additional information:

Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials:

Avoid release to the environment.

14. TRANSPORT INFORMATION

14.1 UN number

UN number: UN1263

14.2 UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3 Transport hazard class

Transport class: 3

14.4 Packaging group

Packing group:

14.5 Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6 Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3



HEALTH AND SAFETY DATA SHEET
Revised 21/06/2017

Page 9

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Contains no substances with Annex XVII restrictions. Rocket additive is not on the REACH Candidate List. Contains no substance on the REACH candidate list. Contains no REACH Annex XIV substances

VOC content: 844 g/l

Seveso Information: This product is subject to the Seveso Directive

15.2 Chemical safety assessment

No chemical safety assessment has been carried out.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H225 Highly flammable liquid and vapour

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H332 Harmful if inhaled

H336 May cause drowsiness or dizziness

H341 Suspected of causing genetic defects

H360FD May damage fertility. May damage the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H411 Toxic to aquatic life with long lasting effects

R10 Flammable

R11 Highly flammable

R20 Harmful by inhalation

R20/21 Harmful by inhalation and in contact with skin

R38 Irritating to skin

R43 May cause sensitisation by skin contact

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R60 May impair fertility

R61 May cause harm to the unborn child

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

R68 Possible risk of irreversible effects

F Highly flammable

N Dangerous for the environment

Xi Irritant

Xn Harmful.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

