

ULTRIMAX

Pre Catalysed Lacquer

TECHNICAL DATA

PRODUCT DESCRIPTION	Pre-Catalysed lacquers are designed for use on general domestic and light use office furniture. They are not suitable for use in high humidity environments where an acid-catalysed product would be more suitable.
👁️ FEATURES	A panel with 2 coats of a similar product has been tested to and has met the General use requirements of BS.6250 on horizontal surfaces.
✓ RECOMMENDED USE	Most wood and wood based substrates except MDF.
📏 PHYSICAL PROPERTIES	MIXING RATIO: n/a COLOUR: Clear GLOSS: 30% VISCOSITY: 40 sec B4 @ 20°C VOC CONTENT: 710 grams per ltr WEIGHT SOLIDS: 22% FLASH POINT: Below 22°C POT LIFE: n/a COVERAGE: 8-10m ² per litre.
📏 FILM THICKNESS	WET FILM THICKNESS: 100 microns DRY FILM THICKNESS: 20 microns
☑️ SURFACE PREPARATION	Ensure all surfaces to be coated are clean, dry and free from contamination.
🔧 APPLICATION METHODS	1 coat by conventional spray application over a suitable basecoat. May also be applied coat on coat to a maximum 3 coats without a basecoat.
🏠 STORAGE LIFE	12 months from manufacture date.
🕒 DRYING / OVERCOATING	Touch-dry 15 mins. Hard-dry 60 mins. CURING TIMES: n/a
💧 THINNERS	Ultrimax Thinners.
⊕ HEALTH & SAFETY	Please refer to the material safety data sheets for further information.

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.